

## 2. 产品图纸 (Product Drawings)

RoHS
  HF
  REACH

|    |       |
|----|-------|
| 1  | LEDA  |
| 2  | LEDK  |
| 3  | LEDK  |
| 4  | GND   |
| 5  | IOVCC |
| 6  | VCC   |
| 7  | RESET |
| 8  | TE    |
| 9  | SDA   |
| 10 | SCK   |
| 11 | CS    |
| 12 | PCLK  |
| 13 | DE    |
| 14 | VSYNC |
| 15 | HSYNC |
| 16 | DB0   |
| 17 | DB1   |
| 18 | DB2   |
| 19 | DB3   |
| 20 | DB4   |
| 21 | DB5   |
| 22 | DB6   |
| 23 | DB7   |
| 24 | DB8   |
| 25 | DB9   |
| 26 | DB10  |
| 27 | DB11  |
| 28 | DB12  |
| 29 | DB13  |
| 30 | DB14  |
| 31 | DB15  |

正视图

75

白色背光板  
连接板: FH26W-31S-0\_3SHH (60)

侧视图

背视图

NOTE:

- DISPLAY TYPE: 2.76" TFT, Normally Black
- DRIVER IC: S17701S
- VIEWING DIRECTION: FREE
- OPERATING TEMPERATURE: -20° C~+70° C.
- STORAGE TEMPERATURE: -30° C~+80° C.
- BACKLIGHT TYPE: 4 WHITE LEDS.
- LED: I<sub>f</sub>=20.0mA/LED (CONSTANT CURRENT).

| REVISION RECORD |    | DATE      | <div style="display: flex; align-items: center;"> <div> <p>SHENZHEN NISIN OPTOELECTRONICS CO., LTD</p> <p>DRAW TYPE : <span style="border: 1px solid black; padding: 2px;">ASSY-Outline</span></p> </div> </div> |  |
|-----------------|----|-----------|--|--|
| △               | 初版 | 2024.6.21 |  |  |
| △               |    |           | CHECKED  |  |
| △               |    |           | APPROVED   |  |

|                  |                |
|------------------|----------------|
| Ver. : v00       | SCALE : N.T.S. |
| DATE : 2024.6.21 | UNIT : mm      |
| DATE             | PRO.(3)        |
| DATE             | SHEET : 1/1    |