



NOTES:

- DRIVING IC: CO5300AF-05, POWER IC: BV6802A
- (CHANNEL SELECT: S1-S90, S151-S240)
- TOUCH IC: CST820
- DISPLAY MODE: 1.78" 368*448 AMOLED (Oncell)
- MEANS DIMENSION FOR REFERENCE
- Light sensibility: 500cd/m(MIN), 550cd/m(TYP), 色度White(X,Y): 0.30±0.02; Y = 0.31±0.02;

TP PIN DESCRIPTION	
TP	SYMBOL
1	TP_VDD
2	TP_INT
3	TP_RST
4	TP_SDA
5	TP_SCL
6	TP_GND

CONT DISPLAY MODULE	
NO.	Symbol
1	VCI_EN
2	GND
3	TP_12C_SDA
4	TP_12C_SCL
5	NC(TP_SWDIO)
6	TP_RST
7	TP_INT
8	TP_VDD(2.8V)
9	GND
10	LCD_RST
11	LCD_TE
12	GND
13	VIO18(1.8V)
14	VIO18(1.8V)
15	NC(VPP)
16	NFC_ANT2
17	NFC_ANT1
18	GND
19	SPI_SDO
20	SPI_SDI
21	SPI_DCX
22	SPI_CLK
23	SPI_CS
24	GND
25	MIPI_CLKP
26	MIPI_CLKN
27	GND
28	MIPI_DOP
29	MIPI_DON
30	GND
31	VPH_PWR(3.8V)
32	VPH_PWR(3.8V)
33	GND
34	GND

REVISION RECORD		DATE	DRAW TYPE :		DRAW NO. : NS178CA3001AZ01	
△1	初版	20240426	总成-Outline		Ver. : V03	SCALE : N.T.S.
△2	修改连接器型号及听筒孔尺寸	20240428	DRAWN	LSL	DATE	20240719
△3	FPC外形和焊盘微调	20240509				
△4	修改盖板正面保护膜	20240719	CHECKED		DATE	PRO.(3)
△5						
△6			APPROVED		DATE	SHEET : 1/1

NISIN SHENZHEN NISIN OPTOELECTRONICS CO., LTD